



NEW

CALPAR™ 4GIII 4 cSt API Group III Base Stock

CALPAR 4GIII is a high quality, very high viscosity index (VHVI) oil engineered to meet the API requirements for Group III base stock. Calpar 4GIII base stock is designed for today's formulating challenges in automotive and industrial lubricant applications including engine oils, transmission and driveline fluids.

CALPAR 4GIII base stock offers:

- Low Volatility
- Very High Viscosity Index
- Excellent Low Temperature Properties
- Outstanding Oxidation/Thermal Stability
- Made in the USA

PRODUCT DATA SHEET

PHYSICAL PROPERTIES	UOM	ASTM METHOD	TYPICAL
VISCOSITY @ 40°C	cSt	D445	20.73
VISCOSITY @ 100°C	cSt	D445	4.38
VISCOSITY @ 100°F	SUS	D2161	108.5
VISCOSITY @ 210°F	SUS	D2161	41.0
VISCOSITY INDEX		D2270	122
API GRAVITY @ 60°F		D4052	37.0
FLASH POINT, COC	°F	D92	440
POUR POINT	°F	D97	-5
COLOR, ASTM		D1500	L0.5
NEUTRALIZATION NUMBER	mg KOH/g	D974	0.013
SATURATES	Mass %	D2007	97.0
SULFUR	Mass %	D4294	0.0015
WATER CONTENT, KARL FISCHER	ppm	D6304	10
COLD CRANK @ -25°C	cPs	D5293	1045
COLD CRANK @ -30°C	cPs	D5293	1750
NOACK VOLATILITY	Mass %	D5800	13.4

SHIPPING LOCATIONS

Shreveport, LA
Burnham, IL

TECHNICAL ASSISTANCE

For product or technical questions contact your Sales Representative or Calumet Product Support.

Product Support:
1-800-437-3188

www.calumetlubricants.com