



CALPAR™ Paraffinic Base Stocks

PRODUCT DATA SHEET

CALPAR GRADES

PHYSICAL PROPERTIES	ASTM Method	60	75	100	325	600	2500
API Group		Group I	Group II	Group II	Group II	Group I	Group I
Viscosity, SUS @ 100°F	D2161	55.4	77.3	106.7	330.9	616.4	2584.5
Viscosity, SUS @ 210°F	D2161	34.1	37.1	40.0	54.2	70.4	155.5
Viscosity, cSt @ 40°C	D445	8.5	13.7	20.4	63.9	117.9	482.3
Viscosity, cSt @ 100°C	D445	2.3	3.2	4.1	8.3	12.7	31.8
Viscosity Index	D2270	73	95	99	98	99	97
API Gravity @ 60°F	D4052	35.0	34.7	33.3	30.6	29.7	27.1
Flash Point, °C	D92	161	192	204	249	267	303
Flash Point, °F	D92	322	379	400	481	513	578
Pour Point, °C	D97	-51	-17	-16	-12	-10	-8
Pour Point, °F	D97	-60	2	4	9	14	19
Color	D1500	L0.5	L0.5	L0.5	L1.0	L2.0	L3.5
Aniline Point, °C	D611	93.5	101.7	104.9	115.0	123.5	133.0
Aniline Point, °F	D611	200.3	215.1	220.6	239.0	254.4	271.5
Saturates, Mass %	D2007	92.2	95.5	95.7	92.8	88.7	88.8
Sulfur, Mass %	D4294	0.0007	0.0008	0.0011	0.0020	0.0007	0.0057

PACKAGING & SHIPPING

Shipped in trucks or rail cars.
Drums/Totes available upon special request.

Shipping Locations:

- Shreveport, Louisiana
- Burnham, Illinois

TECHNICAL ASSISTANCE

For product or technical questions, contact your Sales Representative or Calumet Product Support.

Product Support:
800-437-3188
technical@clmt.com

www.calumetspecialty.com

Calumet Can Custom Blend to Meet Specific Customer Requirements